

## HIGHTEC MARINE 12 SAE 40

HIGHTEC MARINE 12 SAE 40 is a multifunctional trunk piston engine oil.

### Description

HIGHTEC MARINE 12 SAE 40 is a multifunctional trunk piston engine oil for highly rated diesel engines operated on distillate fuel.

### Application

HIGHTEC MARINE 12 SAE 40 is designed for medium speed trunk piston engines operating on distillate fuels. For use in the latest generation of medium-speed 4-stroke trunk piston engines as well as older engine types.

### Benefits

- Very good engine cleanliness
- Resists thermal & oxidative stress
- Advanced high temperature deposit control
- Strong TBN retention

### The quality of this product is equivalent to EU regulations

- API CF
- Daihatsu
- Yanmar

### Typical characteristics

Property	Method	Unit	Value
Density at 15 °C	ASTM D-7042	g/ml	0.8757
Kinematic viscosity KV 40	ASTM D-7042	mm <sup>2</sup> /s	118,0
Kinematic viscosity KV 100	ASTM D-7042	mm <sup>2</sup> /s	14,3
Flash point	ASTM D-92 / DIN EN ISO 2592	°C	270
Pour point	ASTM D-97 / DIN EN ISO 3016	°C	-15
Total base number	DIN 51639-1	mgKOH/g	12,0

The characteristics shown are typical of current production. This data cannot be constructed as a legally binding warranty or guaranty of certain product properties or of the suitability of the product for a specific application. ROWE products are continually improved. Therefore ROWE reserves the right to change all the technical data in this product information at any time without notice. All sales and deliveries shall be subject to our current General Terms and Conditions of Sale and Terms ([www.rowe-oil.com](http://www.rowe-oil.com)).

