

HIGHTEC ANTIFREEZE READY-MIX -25 °C

Premium radiator antifreeze ready-mix free of nitrite, amine and phosphate.

Description

HIGHTEC ANTIFREEZE READY-MIX -25 °C is a premium radiator antifreeze ready-mix free of nitrite, amine and phosphate (ready to use). It reliably protects against deposits, corrosion and foam in cast iron and aluminium engines in accordance with the manufacturer's instruction.

Application

HIGHTEC ANTIFREEZE READY-MIX -25 °C has been developed to meet the requirements of aluminium and cast iron engines. It reliably protects against deposits, corrosion and foam formation and thus ensures optimal heat dissipation. It is used in many internal combustion engines according to the manufacturer's specification. HIGHTEC ANTIFREEZE READY-MIX -25 °C can be used immediately and provides reliable protection at temperatures as low as -25°C without further dilution.

The quality of this product is equivalent to EU regulations

- ASTM D3306/D4985
- SAE J1034

Additionally this product is recommended when the following filling instructions are required

- JIS K 2234
- Erfüllt die Korrosionsschutzanforderungen der / Meets corrosion protection requirements of VW TL 774-C (G11)

Benefits

- Ready-mix - ready for immediate use
- Reliable antifreeze protection at temperatures as low as -25°C
- Reduction in the risk of incorrect filling
- Elimination of problems caused by unsuitable water quality or a false mixing ratio
- Available for use in cast iron and aluminium engines
- Prevention of deposits in a reliable manner
- Very good and permanent corrosion protection
- Unsurpassed protection against cavitation
- Minimal tendency to foam
- Miscible and compatible with other antifreeze agents of the same specification. However, in order to exploit the full product benefits of HIGHTEC ANTIFREEZE READY-MIX -25 °C, a complete coolant change is recommended.

Typical characteristics

Property	Method	Unit	Value
Density at 20 °C	ASTM D1122	g/ml	1.07
Color	visuell	-	blau / blue
Flash point	ASTM D-92 / DIN EN ISO 2592	°C	> 100
Boiling point	ASTM D 1120	°C	~ 104
pH	ASTM D1287	-	7,8 - 8,5
Freezing point	ASTM D1177	°C / °F	-25 / -13

The characteristics shown are typical of current production. This data cannot be constructed as a legally binding warranty or guaranty of certain product properties or of the suitability of the product for a specific application. ROWE products are continually improved. Therefore ROWE reserves the right to change all the technical data in this product information at any time without notice. All sales and deliveries shall be subject to our current General Terms and Conditions of Sale and Terms (www.rowe-oil.com).

