

HIGHTEC TOPGEAR FE SAE 75W-80 S

Fully synthetic gearbox oil with reduced cold viscosity for excellent fuel efficiency. Specially adapted to the wear protection and cold shifting requirements of modern passenger car manual gearboxes.

Description

HIGHTEC TOPGEAR FE SAE 75W-80 S is a fully synthetic high-performance manual gearbox oil with reduced cold viscosity for optimised gearbox efficiency and cold shifting characteristics. It is based on fully synthetic poly-alpha-olefins (PAO) and esters in conjunction with the most advanced additive technology.

Application

HIGHTEC TOPGEAR FE SAE 75W-80 S is used in a modern passenger car manual gearboxes according to the manufacturer's specifications. The reduced viscosity and the optimised viscosity-temperature behaviour enable a significant reduction in fuel consumption and CO2 emissions with smooth shifting characteristics and low shifting power at the same time.

The quality of this product is equivalent to EU regulations

- API GL-4/-5

Additionally this product is recommended when the following filling instructions are required

- BMW MTF LT-1/-2/-3/-4
- Fiat 9.55550-MZ2
- Ford WSS-M2C200-D2
- MB 235.10
- PSA 9730 A2/A8/B 71 2330
- Toyota JWS 227
- VW G009 317/G052 171/G52 178/G052 512/G052 532/G052 527/G052 726/G052 798/G055 726

Benefits

- Reduced cold viscosity for excellent fuel efficiency
- Economy grade for modern passenger car manual gearboxes according to the manufacturer's specification
- Very good protection against wear and corrosion
- High temperature and oxidation stability due to fully synthetic base oils and special additives
- Extremely stable to shear stress - 'Stay-in-grade'
- Stable lubricating film, even with very hot oil and under very high loads. As a result, reduced wear and lower gearbox noise

- Excellent cold viscosity ensures improved shifting ability, fast lubrication and low 'cold wear'

- Miscible and compatible with conventional and synthetic gearbox oils. However, in order to exploit the full product benefits of HIGHTEC TOPGEAR FE SAE 75W-80 S, a complete gearbox oil change is recommended.

Notices

HIGHTEC TOPGEAR FE SAE 75W-80 S is not suitable for use in 'stepped' automatic transmissions, in DCT/DSG transmissions (with dual-clutch running in oil bath) or CVT (continuously variable or 'non-stepped' automatic) transmissions.

Typical characteristics

Property	Method	Unit	Value
Density at 15 °C	ASTM D-7042	g/ml	0,854
Kinematic viscosity KV 40	ASTM D-7042	mm ² /s	37,8
Kinematic viscosity KV 100	ASTM D-7042	mm ² /s	7,5
Viscosity index	ASTM D-7042	-	173
Flash point	ASTM D-92 / DIN EN ISO 2592	°C	180
Pour point	ASTM D-97 / DIN EN ISO 3016	°C	-44

The characteristics shown are typical of current production. This data cannot be constructed as a legally binding warranty or guaranty of certain product properties or of the suitability of the product for a specific application. ROWE products are continually improved. Therefore ROWE reserves the right to change all the technical data in this product information at any time without notice. All sales and deliveries shall be subject to our current General Terms and Conditions of Sale and Terms (www.rowe.com.de).

Are you looking for the correct oil for your vehicle? Scan this code for the ROWE-oilfinder.



25066 | 12.12.2018