

HIGHTEC CLP 320 SYNTH

High - performance synthetic Industrial Gear Oil

Description

HIGHTEC CLP 320 SYNTH is a synthetic industrial gear lubricant offering outstanding lubrication performance under severe operating conditions, including reduced friction and long service life for optimal gear protection.

HIGHTEC CLP 320 SYNTH is formulated to have excellent load carrying capacity and micropitting performance providing long component life even under shock loading conditions. HIGHTEC CLP 320 SYNTH also have excellent corrosion protection, even in the presence of contamination by water and solids.

HIGHTEC CLP 320 SYNTH is formulated using an advanced additive system in combination with specially selected synthetic base fluids to provide outstanding resistance to breakdown over long duration and/or high temperature operation.

HIGHTEC CLP 320 SYNTH has excellent water separation properties, such that excess water can be drained easily from lubrication systems to help extend the life of the gears and ensure efficient lubrication of the contact areas.

Application

HIGHTEC CLP 320 SYNTH is recommended for the use in highly stressed industrial gears such as:

- Enclosed industrial gear systems
- Lubrication of bearings and other components in circulating and splash-lubricated systems
- Certain systems where extra long life is required, maintenance is infrequent or systems are inaccessible.

The quality of this product is equivalent to EU regulations

- DIN 51517-3

Typical characteristics

| Property | Method | Unit | Value |
|------------------------------------|-----------------------------|--------------------|-------|
| Density at 15 °C | ASTM D-7042 | g/ml | 0,86 |
| Kinematic viscosity KV 40 | ASTM D-7042 | mm ² /s | 320 |
| Viscosity index | ASTM D-7042 | - | 145 |
| Pour point | ASTM D-97 / DIN EN ISO 3016 | °C | -42 |
| Copper corrosion 100 A3 | DIN 51759 | Ranking | 1 |
| Steel corrosion, A=distilled water | DIN 51585 | Ranking | 0-A |
| FZG A/8.3/90 (min) | DIN 51354/2 | SKS | >12 |
| Flash point COC | DIN ISO 2592 | °C | >240 |

The characteristics shown are typical of current production. This data cannot be constructed as a legally binding warranty or guaranty of certain product properties or of the suitability of the product for a specific application. ROWE products are continually improved. Therefore ROWE reserves the right to change all the technical data in this product information at any time without notice. All sales and deliveries shall be subject to our current General Terms and Conditions of Sale and Terms (www.rowe.com.de).

Benefits

- Excellent load carrying capacity and micropitting performance
- Very good anti wear properties
- Excellent water separation properties
- Very good corrosion protection
- High thermal stability and oxidation resistance

Recommendation

- Meets the CLP requirements according to DIN 51517-3
- Meets the ISO 12925-1 Type CKD specification

Are you looking for the correct oil for your vehicle?
Scan this code for the ROWE-oilfinder.



40041 | 26.05.2017