

HIGHTEC VDL 68

Compressor oil in compliance with DIN 51506 VDL

Description

HIGHTEC VDL 68 is manufactured with premium solvent raffinates that are resistant to ageing and have high oxidation stability. HIGHTEC VDL 68 contains additives that guarantee good wear protection and protect against oxidation residues and corrosion. HIGHTEC VDL 68 meets the requirements of many compressor manufacturers as well as DIN 51506 VDL.

Recommendation

HIGHTEC VDL 68 is recommended for use in reciprocating and screw compressors.

The quality of this product is equivalent to EU regulations

- DIN 51 506 VDL

Typical characteristics

Property	Method	Unit	Value
Density at 15 °C	ASTM D-7042	g/ml	0,879
Kinematic viscosity KV 40	ASTM D-7042	mm ² /s	68
Viscosity index	ASTM D-7042	-	107
Flash point	ASTM D-92 / DIN EN ISO 2592	°C	>220
Pour point	ASTM D-97 / DIN EN ISO 3016	°C	-30

The characteristics shown are typical of current production. This data cannot be constructed as a legally binding warranty or guaranty of certain product properties or of the suitability of the product for a specific application. ROWE products are continually improved. Therefore ROWE reserves the right to change all the technical data in this product information at any time without notice. All sales and deliveries shall be subject to our current General Terms and Conditions of Sale and Terms (www.rowe.com.de).

Are you looking for the correct oil for your vehicle? Scan this code for the ROWE-oilfinder.



45007 | 11.03.2019