

## HIGHTEC VDL 150

Compressor oil in compliance with DIN 51506 VDL

### Description

HIGHTEC VDL 150 is manufactured with premium solvent raffinate that are resistant to ageing and have high oxidation stability. HIGHTEC VDL 150 contains additives that guarantee good wear protection and protect against oxidation residues and corrosion. HIGHTEC VDL 150 meets the requirements of many compressor manufacturers as well as DIN 51506 VDL.

### Recommendation

HIGHTEC VDL 150 is recommended for use in reciprocating and screw compressors.

**The quality of this product is equivalent to EU regulations**

- DIN 51 506 VDL

### Typical characteristics

Property	Method	Unit	Value
Density at 15 °C	ASTM D-7042	g/ml	0,885
Kinematic viscosity KV 40	ASTM D-7042	mm <sup>2</sup> /s	150
Kinematic viscosity KV 100	ASTM D-7042	mm <sup>2</sup> /s	14,5
Viscosity index	ASTM D-7042	-	95
Flash point	ASTM D-92 / DIN EN ISO 2592	°C	>240
Pour point	ASTM D-97 / DIN EN ISO 3016	°C	-15

The characteristics shown are typical of current production. This data cannot be constructed as a legally binding warranty or guaranty of certain product properties or of the suitability of the product for a specific application. ROWE products are continually improved. Therefore ROWE reserves the right to change all the technical data in this product information at any time without notice. All sales and deliveries shall be subject to our current General Terms and Conditions of Sale and Terms ([www.rowe-oil.com](http://www.rowe-oil.com)).

