

HIGHTEC COOL MMU 3

All-purpose, water-miscible cooling lubricant for machining

Description

HIGHTEC COOL MMU 3 is a water-miscible cooling lubricant (free of boron) containing mineral oils with selected EP/AW corrosion protection agents.

Application

HIGHTEC COOL MMU 3 forms a milky, stable emulsion when mixed with water. HIGHTEC COOL MMU 3 is recommended for the machining of cast iron, steel, non-ferrous metals and partly for aluminum as well.

Benefits

Characteristics

- Good emulsion stability
- Long service life
- Suitable for all applications
- Good starting ability, even with cold mixing water
- It does not contain any secondary alkanol amines and thus complies with TRGS 611
- Chlorine-free

Recommendation

Field of application:

- Machining (drilling, turning, milling)
- Grinding

Recommended concentration to be used:

Machining 5-10%
Grinding process: 4%

Notices

Storage:

When stored in dry, frost-free rooms and in original, unopened containers the storage period is: 9 months
Temperature range: 10-35°C

Degreasing:

HIGHTEC COOL MMU 3 can be degreased using conventional degreasing media, for example by spray cleaning or immersion cleaning with aqueous-alkaline cleaning agents.

Mixing temperature range:

15-20°C

Typical characteristics

Property	Method	Unit	Value
Density at 20 °C	ASTM D1122	g/ml	0.929
Color of the emulsion	visuell	-	milky-opaque
Refractometer factor	-	-	0,85
pH of a 3% emulsion	-	-	8,8
Mineral oil content	-	Gewichts-%	>50
pH of a 5% emulsion	DIN 51369	-	8,9
pH of a 10% emulsion	DIN 51369	-	9,1
Corrosion protection (chip test) grade 0	DIN 51360/2	%	4

The characteristics shown are typical of current production. This data cannot be constructed as a legally binding warranty or guaranty of certain product properties or of the suitability of the product for a specific application. ROWE products are continually improved. Therefore ROWE reserves the right to change all the technical data in this product information at any time without notice. All sales and deliveries shall be subject to our current General Terms and Conditions of Sale and Terms (www.rowe-oil.com).

