

## HIGHTEC DEFOAMER-A

De-foaming agent for aqueous working fluids

### Description

HIGHTEC DEFOAMER-A is an effective de-foaming agent for water-miscible cooling lubricants with or without mineral oils. HIGHTEC DEFOAMER-A is free of secondary alkanol amines and biocides containing amines.

### Application

HIGHTEC DEFOAMER-A is premixed with water or the emulsion ready for use and added to the system where there is sufficient turbulence for adequate mixing (but not in front of the filter). The de-foaming agent is added in portions.

### Benefits

- Pronounced de-foaming properties
- Low consumption
- High effectiveness

### Typical characteristics

Property	Method	Unit	Value
Density at 20 °C	ASTM D1122	g/ml	1.063

The characteristics shown are typical of current production. This data cannot be constructed as a legally binding warranty or guaranty of certain product properties or of the suitability of the product for a specific application. ROWE products are continually improved. Therefore ROWE reserves the right to change all the technical data in this product information at any time without notice. All sales and deliveries shall be subject to our current General Terms and Conditions of Sale and Terms ([www.rowe-oil.com](http://www.rowe-oil.com)).

### Recommendation

Recommended concentration to be used: 0.01-0.02% (maximum concentration to be used: 0.05%)

### Notices

#### Storage

- When stored in dry, frost-free rooms and in original, unopened containers the storage period is: 2 months
- Temperature range: 10-40°C

